

(19) World Intellectual Property  
Organization  
International Bureau



533 480

(43) International Publication Date  
13 May 2004 (13.05.2004)


PCT

(10) International Publication Number  
WO 2004/039280 A1

- (51) International Patent Classification<sup>7</sup>: A61C 8/00 (74) Agent: HARRISON GODDARD FOOTE, 31 St. Saviourgate, York YO1 8NQ (GB).
- (21) International Application Number: PCT/GB2003/004521 (81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (22) International Filing Date: 20 October 2003 (20.10.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 0225065.2 29 October 2002 (29.10.2002) GB
- (71) Applicant (*for all designated States except US*): NEOSS LIMITED [GB/GB]; Yorkshire House, Greek Street, Leeds LS1 5SZ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): ENGMAN, Fredrik [SE/SE]; Haggvagen 19, S-435 37 Møllynycke (SE).
- (84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

[Continued on next page]

(54) Title: MULTIPLE USE IMPRESSION COPING



(57) **Abstract:** A dental impression coping which includes a set of components including an attachment screw access means through the impression material and not more than one attachment screw, that may be used for both pick-up type (open tray) or transfer tray (closed tray) impression moulding techniques. The impression components include an impression coping having non-rotational features and height specific retention means having an outer surface with its bottom end configured to reside preferably below the gingiva surrounding the implant. Means exist on the impression coping, to attach the impression coping to the implant for use in a transfer type impression application. By providing a means to access the attachment screw through the impression material a second impression application, the pick-up type impression application, can be performed, using the same screw that can be used also for the first impression application the transfer type impression application.

WO 2004/039280 A1



**Published:**

— *with international search report*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*